

ELEKTRISCH BEHEIZBARER TANKCONTAINER | ELECTRICALLY HEATED TANK CONTAINER



24.000 Liter isolierter ortsbeweglicher Tankcontainer, Typ T11, (L4BN), doppelt zertifiziert
24,000 liter insulated portable tank container, type T11, (L4BN), dual certified

Technische Daten | technical details

■ Typ Type	Odyssey Design Collar Tank Odyssey design collar tank	■ Maximal zulässiger Betriebsüberdruck Maximum allowable working pressure	4,00 bar 4.00 bar
■ Nominale Kapazität Nominal Capacity	24.000 l 24,000 l	■ Testdruck Test pressure	6,00 bar 6.00 bar
■ Gesamtgewicht Max. gross weight	36.000 kg 36,000 kg	■ Dampfheizung maximal zulässiger Betriebsüberdruck Steam Heating maximum allowable working pressure	4,00 bar 4.00 bar
■ Eigengewicht Tare Weight	3.810 kg 3,810 kg	■ Effektive Dampfheizfläche Effective steam heating surface	12 m ² 12 m ²
■ Länge Lenght	6.058 mm 6,058 mm	■ Dampfheizung Testdruck Steam heating test pressure	6,00 bar 6.00 bar
■ Breite Width	2.438 mm 2,438 mm	■ Werkstoff Shell material	Edelstahl 316L to SANS 50028-7 Typ 1.4402 / 1.4404 EN 10028-7 Typ 1.4404 Stainless steel 316L to SANS 50028-7 Type 1.4402 / 1.4404 EN 10028-7 Type 1.4404
■ Höhe Height	2.591 mm 2,591 mm	■ Isolierung Insulation	Nenndicke 50 mm, bestehend aus Polyurethanplatten (33 mm) über einer mit Folie kaschierten Mineralwolle (17 mm) Nominal thickness 50 mm consisting of 33 mm polyurethane panels over 17 mm compressed foil backed mineral wool
■ Stärke der Tankwand Shell manufacturing thickness	4,60 mm 4.60 mm	■ Elektrische Heizung Electrically Heating	400 V / 18 kW Eltherm, 4 Pin 32 A CEE Reefer-Plug 400 V / 18 kW Eltherm, 4 poliger 32A CEE Reefer-Stecker
■ Max. Betriebstemperatur Max. Tank operating temperature	150°C 150°C		
■ Metallurgische Auslegungstemperatur Metallurgic Design Temperatur for Tank	-40°C bis +160°C -40°C to +160°C		

Isolierter Tankcontainer mit Klappgeländer und elektrischer Heizung zum Halten der Produkttemperatur während des Transports

Insulated tank container with collapsible handrail and electrically heating for maintaing the product temperature during transport

VTG Rail Europe GmbH
Nagelsweg 34
20097 Hamburg
Germany

Tel.: +49 40 2354-0
info@vtg.com
www.vtg.com

ELEKTRISCH BEHEIZBARER TANKCONTAINER | ELECTRICALLY HEATED TANK CONTAINER



24.000 Liter isolierter ortsbeweglicher Tankcontainer, Typ T11, (L4BN), doppelt zertifiziert
24,000 liter insulated portable tank container, type T11, (L4BN), dual certified

